

		Classic 40 UNT00865	Classic60 UNT00866
Electronic features	Control Panel	Mechanical	Mechanical
	Thermostat Control	Mechanical	Mechanical
Cooling Capacity	Rating Conditions:		
	95° F at 60% RH	39,000 Btu/h	60,000 Btu/h
Electrical	Voltage Requirement	1Phase,220 V	3Phase,380 V
Characteristics	Total Power Consumption	4.7KW	7.2KW
	Current Consumption	14A	10.5 A
	Recommended Fuse Size	25A	20A
	Nema Plug Configuration	L150-30	N/A
	Min.-Max. Voltage	220-240	380-415
Fans	Motor Output-high/low	0.75 kw Evap. 0.40 kw Cond.	0.75 kw Evap 0.4 kw Cond.
	Fan Type	Centrifugal	Centrifugal
Evaporator	Max.Air Flow-high/low	1060 cfm	1580 cfm
	Max. External Static Pressure	1.72 iwq	1.35 iwq
Condenser	Fan Type	Propeller	Propeller
	Max. Air Flow-high/low	2650 cfm	3800 cfm
	Max. External Static Pressure	0.05 iwq	0.05 iwq
Compressor	Type	Hermetic Reciprocal	Hermetic Reciprocal
	Output	2.2 kw	3.75 kw
Refrigerant	R-22 Charge	4.4 lbs	5.9 lbs
Dimensions	WXDXH	.26X43X39 in	32X49X42 in.
Net Weight / Shipping Weight		353 lb/420 lb	463 lb/545 lb
Power Cord	Gauge	12AWG(4-core)	12AWG(4-core)*
	Length	6 ft	N/A
Condensate Tank Capacity		2@5 gal (optional)	N/A
Operating Conditions	(@50%RH)Min.-Max.	75° -115° F	75° -115° F
Max. Duct Length	Per Cold Duct Hose	Varies	Varies
	Hot Duct Hose	40 ft	40 ft
Max. Sound level	With Condenser Duct-high/low	N/A	N/A
	With Condenser Duct-high/low	72db	72db

This model does not come with a power cord.To hard wire the unit,use the specified wire gauge.

اطاقهای کامپیوتر و دیتا روم
مجالس و جشن ها
هوایمای در حال سکون
در محلهای که سیستم تهویه آنها تحت تعمیرند.



شرکت برنولی یکی از بزرگترین و با سابقه ترین شرکتهای تهویه مطبوع در ایران می باشد که بیش از ۴۰ سال سابقه در زمینه تولید ، نصب و راه اندازی انواع سیستم های تهویه مطبوع در ایران دارد.